

LINEA-OUTLINE



TESSUTO-STRETTO

TESSUTO-CARBONE

TESSUTO-GRIGIO

LINEA-STRINGLINE







Commercial Upholstery Fabric





LINEA

Commercial Upholstery Fabric

SPECIFICATIONS

Composition

85% PVC 15% Polyester Gauge: 1.0mm Roll length: 30m Roll width: 137cm

Pattern Direction: Railroaded.

Test method AS 2001.2.25 (12kPa) Abrasion resistance

Martindale method. No significant wear after 50,000+ rubs.

Meets F.R. standards for F.R. properties: Tested to Australian Standards (AS 1530.3)

use in commercial areas Spread of flame: 0 Smoke developed: 5 I.M.O. Standards A. 652 (16)

AS/NZS 3837

Fire test certificates available upon request.

& anti-bacterial

Anti-microbial

Sanitised to inhibit growth of bacteria, mould & mildew.

Colour fastness to light LINEA is UV stabilized and suitable for indoor and outdoor use. Light fastness rating 6-7 ISO 105-B02-1994 (Grey scale 1-5).

Colour fastness to bleach Tested to Australian Standards (AS 2001.4.11)

No change of colour rating 4-5.

LINEA is ROHS certified, restricting the use **ROHS** standards

> of hazardous substances. No formaldehyde, lead, mercury & chromium is used in the manufacturing process.

A protective top surface allowing easy removal of difficult Protech

stains and dirt.

Suitable for heavy commercial upholstery, marine, Usage

healthcare & screens.

CARE & CLEANING

Most stains can be cleaned using warm soapy water, followed by clean water rinsing. Moderate scrubbing with a medium bristle brush will help loosen soiling from the embossed surface. Failure to follow cleaning instructions may permanently stain and reduce the life of the vinyl. For further cleaning information, please contact Austex Fabrics for a product cleaning guide.



All Austex products are designed and manufactured in accordance with the quality assurance system ISO 9001.



FIRE RETARDANT



MOULD & MILDEW RESISTANT



UV STABILISED





STAIN RESISTANT



ENVIRONMENTALLY FRIENDLY





OUTDOOR





